



## SPECIALTY DOORS Fully Gasketed Access Door **AS-9000**

### Application

- Designed to provide a fully gasketed fit in all types of walls and ceilings
- This door is commonly used in clean rooms, laboratories, operating rooms, etc.

### Product Features

- Fully gasketed access door
- Formed door panel with reinforced edges and a concealed hinge, along with closed cell gasket between the door and frame

### AS-9000 Access Door Specifications:

**Door / Door Frame:** Stainless Steel or Steel: 18 gage door, 18 gage mounting frame, flange to be 1" wide

**Hinge:** Concealed

**Gasket:** Pemko S88 1/8" x 3/8" opened cell gasket

**Standard Latch:** Stainless steel screwdriver operated cam latch

**Optional Latches/Locks:** Cylinder lock & key, allen head cam latch, spanner head cam latch

**Finish:** Stainless steel: #4 satin polish. Steel: 5 stage iron phosphate with prime coat of White alkyd baked-on enamel

Please note the AS-9000 has not been tested for air penetration. For a door that has been tested for Air & Water penetration see the ADWT on page 11.



### STANDARD SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR	
inches	mm	lbs.	kg.
12 X 12	305 X 305	6	2.7
18 X 18	457 X 457	11.5	5.1
24 X 24	610 X 610	19	8.4
24 X 36	610 X 914	28	12.4

Wall or ceiling opening is nominal door size + 3/8" (9 mm)  
For detailed specifications see submittal sheet

