SUBMITTAL: MODEL CT™ TRIMLESS FLUSH ACCESS PANELS

PAGE 1 OF 2

An Access Panel with Recessed Door and Trimless Frame with 14 Gauge Frame.

Designed to accommodate an insert up to 1/2" thickness in the door. Acoustic, ceramic tile or drywall can be attached to the door with adhesive to be flush with the surrounding tile field. A continuous hinge, located at the outside edge of the door ensures easy opening of the plaster or tile covered panel. Not to be used for suspended ceilings.

SPECIFICATIONS:

Door Panel: 16 gauge steel, recess to accommodate 1/2" thick insert.

Frame: 14 gauge steel


Finish: White powder coat paint.

Hinge: Recessed, continuous hinge mounted on the long side of oblong panels.

Lock: Flush screwdriver-operated steel cam standard "C"

Sizes: Minimum 6" x 6". Maximum walls—36" x 36", ceilings—24" x 48"







Recessed Door Accepts 1/2" Insert

STEP 1: SELECT MODEL NUMBER AND QUANTITY ON CHART ON PG 2, OR ENTER OTHER SIZE BELOW

W x H

STEP 2: SELECT MATERIAL

CT Steel

CTG Galvanneal Steel (Additional Cost)

Order Format Example: CT-2424M2W CT - CTG Width Height Lock (C Std or Optional Lock/Latch Code)

LATCH AND LOCK OPTIONS					
Cylinder Lock (L)	Optional Torx Head Cam (C2)	Optional Spanner Head Cam (C3)	Optional Hex Head Cam (C4)	Mortise Lock (M2)	
	(°	C	0	(3)	

STEP 3: SELECT OPTIONAL FEATURES AT ADDITIONAL COST:

___Optional color Code: _____ - see page 2

(L) Cylinder lock installed

(C2) Torx head cam

(C4) Hex head cam

(C3) Spanner head cam

(M1) Mortise cam lock prep 1-1/8" dia, 1-1/4" length

(M2) Mortise cam lock (06431) installed

14 Gauge frame and 14 gauge door



Standard Cam Latch



JL INDUSTRIES

© 2022 ACTIVAR CONSTRUCTION PRODUCTS GROUP— CT™ IS A TRADEMARK OF ACTIVAR

Distributor:	Quantity:
Contractor:	Approved By:
Model #:	Architect:
Project:	Date:

4/27/2022

ebuildingproducts.com

SUBMITTAL: MODEL CT™ FLUSH ACCESS PANELS

Р	Δ	G	F	2	0	F	2
	$\boldsymbol{-}$	u	_	_	$\mathbf{\sim}$		_

	A - MODEL SIZE = DOOR SIZE	B - OUTSIDE FRAME DIMENSIONS		SHIPPING WEIGHT	LATCH
QTY	WIDTH X HEIGHT	WIDTH	HEIGHT	APPROX.	(ES)
	12" x 12"	12 1/4 "	12 1/4 "	9 lbs	1
	12" x 24"	12 1/4 "	24 1/4 "	14 lbs	2
	18" x 18"	18 1/4 "	18 1/4 "	15 lbs	3
	22" x 30"	22 1/4 "	30 1/4 "	26 lbs	4
	24" x 24"	24 1/4 "	24 1/4 "	24 lbs	4
	24" x 36"	24 1/4 "	36 1/4 "	34 lbs	5
	36" x 36"	36 1/4"	36 1/4"	51 lbs	6

