



## WHEELED FIRE EXTINGUISHERS - ABC AND STANDARD DRY CHEMICAL (BC)

### Wheeled Dry Chemical

With our comprehensive line, we have your large-scale fire protection needs covered. Available in three size capacities with two choices of extinguishing agent and three different operational design configurations, the best match for your hazard protection needs can be accurately selected, maximizing the fire safety of your operation. Designed for one man operation these units are easily transportable through doorways and over rough terrain. Tow Loops can be added to your selection if you need easy vehicle transport capability. All models are rechargeable and meet relevant UL, ULC, TC & DOT requirements. Selected models have US Coast Guard Approval. Stationary models are also available.

**Typical Uses:** Offshore rigs, ship docks, refineries, chemical plants, aircraft ramps, remote construction sites, large laboratories, processing plants, storage and loading areas. Not for use on sensitive electronic equipment.

### FEATURES:

DOT approved cylinders with chrome plated brass valve assemblies. Cylinders are manufactured to DOT specification 4BW240. Valves are designed and manufactured to Buckeye's rigid standard of quality. | Highly visible pressure-indicating gauge. Cylinders and carriages are shot blasted, primed and coated with the finest polyurethane powder paint finish that exceeds Underwriter's Laboratories 240 hour salt spray requirements. Hoses are included - see chart for sizes. All component parts are replaceable. Tow loops are available upon request. Tow loops allow for low speed (15 MPH) towing over gravel or paved surfaces. All units are equipped with all weather semi-pneumatic 12.3 inch diameter, 3.5 inch wide tires that allows for easy movability through narrow doors and walkways by a single operator. | Built to ANSI/UL 299 and 711 standards.





### Class A,B,C Fires

Portable, large-capacity extinguisher units contain specially-fluidized and siliconized mono ammonium phosphate powder which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

### Class B, C Fires

These models contain a siliconized sodium bicarbonate base, the traditional dry chemical. Cleanup after use is generally easy, because the chemical does not normally bake to a hot metal surface. Non-toxic.



  <p><b>*DOWNLOAD CURRENT SUBMITTAL BEFORE ORDERING*</b> © 2017 ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.</p>	Distributor:	Quantity:
	Contractor:	Approved By:
	Model #:	Architect:
	Project:	Date:
		4/10/17



QTY	MODEL	AGENT CAPACITY	UL/ULC RATING	DISCHARGE TIME	DISCHARGE RANGE	UNIT WEIGHT	HEIGHT	UNIT WIDTH	UNIT DEPTH	HOSE LENGTH & DIAMETER	WHEEL TYPE	WHEEL DIAMETER
<b>DRY CHEMICAL ABC</b>												
	8FW30010*	50 lb. (22.7 kg)	10-A:160-B:C	35 sec	25-35 ft. (7.6-10.7 m)	154 lb. (70 kg)	47 inches (119 cm)	24 inches (61 cm)	26.5 inches (67 cm)	25 ft. x .50 in. (7.6 m x 1.3 cm)	Rubber	12.3 in. x 3.5 in. (31.3 cm x 8.9 cm)
	8FW30110*	125 lb. (56.7 kg)	30-A:240-B:C	47 sec	30-40 ft. (9.1-12.2 m)	300 lb. (136 kg)	51 inches (128 cm)	26 inches (66 cm)	38 inches (96.5 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
	8FW31120	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	387 lb. (176 kg)	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
	8FW31140	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	422 lb. (191 kg)	55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
	8FW31150	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	434 lb. (197 kg)	55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
	8FW31110	125 lb. (56.7 kg)	30-A:240-B:C	43 sec	30-40 ft. (9.1-12.2 m)	325 lb. (147 kg)	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
	8FW32120	300 lb. (136 kg)	30-A:320-B:C	52 sec	30-40 ft. (9.1-12.2 m)	780 lb. (354 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32140	300 lb. (136 kg)	30-A:320-B:C	52 sec	30-40 ft. (9.1-12.2 m)	806 lb. (366 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32110	300 lb. (136 kg)	30-A:320-B:C	53 sec	30-40 ft. (9.1-12.2 m)	657 lb. (298 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32130	300 lb. (136 kg)	30-A:320-B:C	53 sec	30-40 ft. (9.1-12.2 m)	683 lb. (310 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
<b>STANDARD DRY CHEMICAL</b>												
	8FW31220	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	412 lb. (187 kg)	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16.4 in. x 4 in. (40.6 cm x 10.2 cm)
	8FW31240	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	447 lb. (203 kg)	55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
	8FW31250	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	459 lb. (208 kg)	55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
	8FW31210	150 lb. (68 kg)	240-B:C	43 sec	30-40 ft. (9.1-12.2 m)	350 lb. (159 kg)	50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
	8FW32220	350 lb. (159 kg)	320-B:C	59 sec	30-40 ft. (9.1-12.2 m)	830 lb. (376 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32240	350 lb. (159 kg)	320-B:C	59 sec	30-40 ft. (9.1-12.2 m)	856 lb. (388 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32210	350 lb. (159 kg)	320-B:C	50 sec	30-40 ft. (9.1-12.2 m)	707 lb. (321 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
	8FW32230	350 lb. (159 kg)	320-B:C	50 sec	30-40 ft. (9.1-12.2 m)	733 lb. (333 kg)	58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)

\* Coast Guard Approved Models