

Stucco and Plaster


Section: 09200

Factory Assembled Intersections "V" Control Joint

v Control Joint			
Product Number	Ground	Dimensions/Descriptions	Pieces Per Box
2050-AIC	1/2" (13 mm)	Factory assembled Intersections. "V" control joint for inside corners (IC), outside corners (OC), tees (T), and crosses (C).	25
2050-AOC	1/2" (13 mm)		25
2050-AT	1/2" (13 mm)		25
2050-AC	1/2" (13 mm)		25
2058-AIC	5/8" (16 mm)		25
2058-AOC	5/8" (16 mm)		25
2058-AT	5/8" (16 mm)		25
2058-AC	5/8" (16 mm)		25
2075-AIC	3/4" (19 mm)		25
2075-AOC	3/4" (19 mm)		25
2075-AT	3/4" (19 mm)		25
2075-AC	3/4" (19 mm)		25
2078-AIC	7/8" (22 mm)		25
2078-AOC	7/8" (22 mm)		25
2078-AT	7/8" (22 mm)		25
2078-AC	7/8" (22 mm)		25
2100-AIC	1" (25 mm)		25
2100-AOC	1" (25 mm)		25
2100-AT	1" (25 mm)		25
2100-AC	1" (25 mm)		25







Application:

Factory Assembled Intersections reduce labor in the field and provide a better quality finish.

Specification:

Control Joint Intersections shall be Plastic Components, Inc. #______. All exterior accessories shall be of PVC material conforming to ASTM standards D1784, C1063 and D4216. They shall be used where specified by the architect and installed per industry standards.





Caulk all butt joints, intersections and ends.