ebuildingproducts.com

2500 Series



Single Cover



2500 SERIES SPECIFICATIONS

Heavy duty timber floors: Junckers solid hardwood floors, timber strip flooring or heavy-duty laminate flooring.
Pedestrian traffic (including wheeled trolleys, sack trucks etc.) only.
Can be fitted quickly and unobtrusively, ensuring minimum disruption.
Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof.
Fits within a standard timber floor, removing the need to cut rebates underneath the timber flooring.
Provides easy access to underfloor services using lifting keys.
Screwed sideways into the floor to allow movement with a floating timber floor.
See range overview (overleaf)
Approx. 16kg/m ² .

Stainless steel floor access covers for pedestrian traffic on wooden surfaces



info@ebuildingproducts.com



ebuildingproducts.com

All access covers are made to measure to the minimum and maximum dimensions, in either direction, given below. Some covers are available in stock sizes for more urgent deliveries. Contact office for details.

FLOOR ACCESS COVERS REQUIRING INFILL

	LOADING	COVER TYPE	DF	PTH	CLEAR INTER	NAL OPENING	OVERALL	RAME SIZE	FIRE RATED
IARD SURFACES	Bespoke loading available for most hatches. Contact office for details.		Overall Frame Depth	Max. Flooring Thickness	Minimum Dimensions	Maximum Dimensions	Minimum Dimensions	Maximum Dimensions	BS476 Part 2 1987
olid Hardwood, Timber Strip and Heavy Duty Laminates			Α	В		С		D	
00 Series - Stainless Steel	Light - Pedestrian	Single	25mm	22mm	100mm	Contact office	220mm	Contact office	-
ramic Tiles, Marble, Terrazzo, Concrete, Resin, rquet Floors									
000 Series - Aluminium	Light - Pedestrian	Single	50mm	18mm	100mm	750mm	220mm	870mm	1 hour
		Duct	50mm	18mm	100mm span	600mm span	220mm	720mm span	-
		Multipart	50mm	18mm	As required	As required, any length	As required	As required, any length	-
000 Series - Stainless Steel	Light - Pedestrian	Single	50mm	15mm	100mm	750mm	230mm	880mm	1 hour
		Duct	50mm	15mm	100mm span	600mm span	230mm	730mm span	-
		Multipart	50mm	15mm	As required	As required, any length	As required	As required, any length	-
500 Series - Aluminium	Medium - Cars up to 5 Tonnes	Single	75mm	32mm	100mm	900mm	220mm	1020mm	3 hours
		Duct	75mm	32mm	100mm span	900mm span	220mm	1020mm span	2 hours
		Multipart	75mm	32mm	As required	As required, any length	As required	As required, any length	2 hours
'500 Series - Stainless Steel	Medium - Cars up to 5 Tonnes	Single	75mm	40mm	100mm	900mm	230mm	1030mm	3 hours
		Duct	75mm	40mm	100mm span	900mm span	230mm	1030mm span	2 hours
		Multipart	75mm	40mm	As required	As required, any length	As required	As required, any length	2 hours
ER Series - Aluminium (hinged)	Light - Pedestrian	Single	89mm	25mm	610mm	1065mm	814mm	1269mm	-
		Double	89mm	25mm	1220mm	1830mm	1424mm	2034mm	-
R Series - Aluminium (hinged)	Light - Pedestrian	Single	89mm	N/A	597mm	1168mm	962mm	1422mm	2 hours
ISE 75 Series - Aluminium (hinged)	Medium - up to 5 Tonnes	Single	75mm	32mm	550mm*	1000mm*	683mm	1133mm	3 hours
		Duct	75mm	32mm	550mm* span	1000mm* span	683mm span	1133mm span	2 hours
		Multipart	75mm	32mm	Contact office	Contact office	Contact office	Contact office	2 hours
ISE 75 Series - Stainless Steel (hinged)	Medium - up to 5 Tonnes	Single	75mm	40mm	550mm*	1000mm*	697mm	1147mm	3 hours
		Duct	75mm	40mm	550mm* span	1000mm* span	697mm span	1147mm span	2 hours
		Multipart	75mm	40mm	Contact office	Contact office	Contact office	Contact office	2 hours
all types of hard surfaces including External Grade aving Slabs (i.e. Granite and Concrete)					* Size does not includ	le hardware obstructions			
050 Series - Stainless Steel	Heavy - up to 6.5 Tonnes	Single	105mm	70mm	100mm	900mm	230mm	1030mm	3 hours
		Duct	105mm	70mm	100mm span	900mm span	230mm	1030mm span	2 hours
		Multipart	105mm	70mm	As required	As required, any length	As required	As required, any length	2 hours
ree Pit Covers									
i 000 Series - Aluminium	Light - Pedestrian	Tree Pit	50mm	20mm	100mm	750mm	230mm	870mm	-
- Stainess Steel			50mm	22mm	100mm	750mm	230mm	880mm	-
500 Series - Aluminium	Medium - Cars up to 5 Tonnes	Tree Pit	75mm	32mm	100mm	900mm	230mm	1020mm	-
- Stainess Steel			75mm	40mm	100mm	900mm	230mm	1030mm	-
050 Series - Stainless Steel	Heavy - up to 6.5 Tonnes	Tree Pit	105mm	70mm	100mm	900mm	230mm	1030mm	-
LEXIBLE SURFACES	For all types of flexible floo	ring, Vinyl, Linole	eum, Rubber, sor	ne Carpets					
/isedge [®] Series - Aluminium	Light - Pedestrian	Single	50mm	2-4mm	150mm	1000-1200mm	237mm	1137-1337mm	-
		Duct	50mm	2-4mm	150mm span	1000mm span	237mm span any length	1137mm span any length	-
		Multipart	50mm	2-4mm	As required	As required	As required	As required	-
www.howegreen.	com Tel: +44 (0) 1920 46	3 230				www.howe	green.com Tel: +44 (0)	1920 463 230	
						lists Oslaud	Idinanroduc	to 0.000	

855-832-8453

A

1030mm	3 hours
1030mm span	2 hours
As required, any length	2 hours



ebuildingproducts.com

SOLID FLOOR ACCESS COVERS NO INFILL REQUIRED

	LOADING	COVER TYPE	DEPTH		CLEAR INTERNAL OPENING		OVERA
HARD SURFACES	Bespoke loading available for most hatches. Contact office for details.		Overall Frame Depth	Max. Flooring Thickness B	Minimum Dimensions	Maximum Dimensions C	Minimum Dimensions
JFR Fire Doors - Stainless Steel	Light - Pedestrian	Single	89mm	-	610mm	1830mm	826mm
5 Bar Series Tread Plate - Aluminium	Light - Pedestrian	Single Duct	50mm 50mm	-	150mm 150mm clear span	1000mm 1000mm span, any length	287mm 287mm span
J-AL Drainage Doors - Aluminium	Light - Pedestrian	Single Double	89mm 89mm	-	610mm 760mm	1220mm 1830mm	762mm 912mm
J-AL H20 Drainage Doors - Aluminium	Heavy - up to 14.5 Tonnes	Single Double	89mm 89mm	-	610mm 760mm	1065mm 1830mm	762mm 1014mm

SPECIAL APPLICATIONS

We can provide solutions to many unique and special applications. Please contact office to discuss any unusual requirements you may have.

CHANNEL DRAIN SOLUTIONS

_Most types of finish in changing rooms, shower areas, spas, nens, laboratories, veterinary surgeries etc.

HG100 - Stainless Steel (Light - Pedestrian).

HG200 - Stainless Steel (Consult office for details).

DGE TRIMMINGS

HARD AND FLEXIBLE SURFACES

VISEDGE® DS SERIES

nium trim to secure and protect the edge of vinyl/linoleum flooring when laid op of another surface, such as ceramic tiles. It is used to securely anchor the neter of the flexible flooring.

VISEDGE[®] VR SERIES

- nyl edge securing trim with a weldable PVC edge, enabling two differing floor
- ies (eg vinyl and terrazzo) to be finished flush. It prevents the ingress of water
- protects the edge profile of the adjoining flooring.

Visedge® DS and VR Series Edge Trims - Packs of 5 (2m lengths).

FIXED VERTICAL LADDERS

All Ladders: 488mm wide in standard lengths between 2m and 6m. Special sizes available on request.

TYPE BL	- Aluminium - Mild Steel	No safety cage.
TYPE BL-WH	- Aluminium - Mild Steel	Safety cage.
TYPE BL-WG	- Aluminium - Mild Steel	Safety cage and guardrail.


SAFETY AND MAINTENANCE PRODUCTS

LadderUp™ Safety Post	
Cover Skate	
Lifting Key	
Replacement Bolt	

HELP AND ADVICE

Access Cover Sizes

Our diagram below answers the most common questions.



Duct and Mulitpart Design Please contact office for details of beams and pockets.

www.howegreen.com

Tel: +44 (0) 1920 463 230

www.howegreen.com Tel: +44 (0) 1920 463 230 info@ebuildingproducts.com

855-832-8453

ALL F	RAME SIZE	FIRE RATED
	Maximum Dimensions D	BS476 Part 20: 1987
	2046mm	1 hour
	1137mm	-
	1137mm span, any length	•
	1370mm	-
	1982mm	-
	1319mm 2084mm	-

VERALL FRAME DEPTH of access cover A including frame



B MAXIMUM FLOORING THICKNESS for inset to cover



C CLEAR INTERNAL OPENING = size of access gap through frame



D OVERALL FRAME SIZE = footprint of access cover including frame

