
ebuildingproducts.com

FIRE PROTECTION CABINET - ARCHITECTURAL: ACADEMY FIRE-FX2™ SERIES - Aluminum

As a leader in the industry, JL Industries offers an aluminum cabinet: The Architectural Academy Series. Available in multiple tub sizes designed to be compatible with multiple fire extinguishers. Select from a wide variety of options and accessories, this cabinet will meet all your project needs.



SPECIFICATIONS:

Tub Material & Finish:

Steel, white powder coat (recessed & semi-recessed)

Trim Material & Finish: Aluminum, clear anodized Door Material & Finish: Aluminum; clear anodized

Glazing: .090" Clear acrylic

Insulation: Foil-faced mineral wool

Hinge: Continuous hinge, zinc-plated steel, opens to 180°

Hardware: Zinc plated pull handle with roller catch or cylinder Saf-T-Lok™

ADA Compliance: Cabinet cannot protrude more than 4" and the handle cannot be mounted more than 48" above finished floor. Surface-mount and 4-½" trim style do not comply with

FIRE-RATINGS:

ADA.

UL classified and labeled up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/USC-S115.

OPTIONS:

Door: Full, vertical duo, solid, horizontal

Glazing: 1/8" clear tempered, 1/4" clear wired glass, 1/8" bronze acrylic, 1/8" gray acrylic, 1/4" clear laminated safety glass

Handles: Recessed handle, magnetic catch

Alarms: Commander alarm, Brigadier alarm, Strobe alarm

Material: Dark bronze anodized

Finish: Red, black, other powder coat colors **Lettering:** Silkscreen, engraving, etching

ADDITIONAL ACCESSORIES (sold separately)

Die cuts, decals, plastic signs


See supplemental submittals for more information on various options and accessories.

ADA CABINET MOUNTING HEIGHT:

Standard pull on G, E, W, L22 and B door styles with Saf-T-Lok are $3-\frac{1}{2}$ " higher than door center, so allow for that when mounting cabinet.

Standard Pull with no lock or flush pull are centered on door.

Interpretation of fire and building codes may vary. Consult with the local authority having jurisdiction (AHJ) to determine appropriate standards.




ebuildingproducts.com


FIRE PROTECTION CABINET - ARCHITECTURAL: ACADEMY FIRE-FX2™ SERIES - Aluminum


MODEL & TRIM			T	UB I. D.		TRIM	O. D.		L ROU		WT	COMPATIBLE
MODEL	TRIM PROJECTION	≤4"	WIDTH (A)	HEIGHT (B)	DEPTH (C)	WIDTH (E)	HEIGHT (F)	WIDTH (W)	HEIGHT (H)	DEPTH (D)	LBS	FIRE EXTINGUISHERS
C8125	3/8" flat square	✓	9"	18"	5-½"	12-%"	21-¾"	11-5/16"	20-5/16"	6-7/16"	17	Cosmic, Galaxy 2.5 - 6 lb
C8126	1-½" square	✓	9"	18"	5-1⁄2"	12-%"	21-%"	11-5/16"	20-5/16"	5-3/16"	17	(mount 6 lb to tub)
C8127	2-½" rolled	✓	9"	18"	5-1⁄2"	12-%"	21-%"	11-5/16"	20-5/16"	4- ¹³ / ₁₆ "	18	Mercury 2.5 - 5 lb
C1720	2-¼" square	✓	10-1⁄2"	24"	5"	13-%"	27-%"	12-13/16"	26-5/16"	4"	25	Cosmic, Galaxy Mercury 2.5 - 5 lb
C1825	3/8" flat square	✓	10-1⁄2"	24"	5-½"	13-%"	27-¾"	12-13/16"	26-5/16"	6-7/16"	22	
C1826	1-½" square	✓	10-1⁄2"	24"	5-1/2"	13-%"	27-%"	12-13/16"	26-5/16"	5-3/16"	22	Cosmic/Galaxy 2.5 - 6 lb
C1827	3" rolled	✓	10-1⁄2"	24"	5-½"	13-%"	27-%"	12-13/16"	26-5/16"	3-11/16"	22	(mount 6 lb to tub)
C1822	4" rolled w/ rec hndl	✓	10-1⁄2"	24"	5-½"	13-%"	27-%"	12-13/16"	26-5/16"	3-1/2"	25	Mercury 2.5 - 5 lb
C1828	4-½" rolled		10-1⁄2"	24"	5-½"	13-%"	27-%"	12-13/16"	26-5/16"	2-13/16"	27	
C1025	3/8" flat square	✓	10-1⁄2"	24"	6"	13-%"	27-¾"	12-13/16"	26-5/16"	6-15/16"	23	
C1026	1-½" square	✓	10-1/2"	24"	6"	13-%"	27-¾"	12-13/16"	26-5/16"	5-11/16"	23	Cosmic, Galaxy 2.5 - 10
C1027	3" rolled	✓	10-1⁄2"	24"	6"	13-%"	27-¾"	12-13/16"	26-5/16"	4"	24	lb Mercury 2.5 - 5 lb
C1022	4" rolled w/ rec hndl	✓	10-1⁄2"	24"	6"	13-%"	27-¾"	12-13/16"	26-5/16"	4"	25	Sentinel 5 lb
C1028	4-½" rolled		10-1⁄2"	24"	6"	13-%"	27-%"	12-13/16"	26-5/16"	3-5/16"	26	
C2025	3/8" flat square	✓	12"	27"	7-¾"	15-¾"	30-%"	14-5/16"	29-5/16"	8-11/16"	29	Cosmic, Galaxy
C2026	1-¼" square	✓	12"	27"	7-¾"	15-¾"	30-%"	14-5/16"	29-5/16"	7-11/16"	30	(mount 20 lb to tub) Mercury 2.5 - 15 lb
C2027	2-½" rolled	✓	12"	27"	7-3/4"	15-%"	30-%"	14-5/16"	29-5/16"	7-1/16"	31	(mount 15.5 lb to tub)
C2022	4" rolled w/ rec hndl	✓	12"	27"	7-3/4"	15-¾"	30-%"	14-5/16"	29-5/16"	5-¾"	33	Sentinel 5 - 10 lb Grenadier, Saturn,
C2028	4-1⁄2" rolled		12"	27"	7-¾"	15-¾"	30-%"	14-5/16"	29-5/16"	5-1/16"	33	Nebula 270
C3025	3/8" flat square	✓	16"	32"	7-3/4"	19-¾"	35-¾"	18-5/16"	34-5/16"	8-11/16"	43	Cosmic, Galaxy
C3026	1-¼" square	✓	16"	32"	7-¾"	19-¾"	35-%"	18-5/16"	34-5/16"	7-11/16"	43	(mount 20 lb to tub) Mercury 2.5 - 15 lb
C3027	2-½" rolled	✓	16"	32"	7-3/4"	19-¾"	35-%"	18-5/16"	34-5/16"	7-1/16"	45	(mount 15.5 lb to tub)
C3022	4" rolled w/ rec hndl	✓	16"	32"	7-3/4"	19-¾"	35-%"	18-5/16"	34-5/16"	5-3/4"	45	Sentinel 5 - 15 lb Grenadier, Saturn
C3028	4-½" rolled		16"	32"	7-3/4"	19-¾"	35-%"	18-5/16"	34-5/16"	5-1/16"	46	Nebula 250-272
C4025	3/8" flat square	✓	20"	27"	7-3/4"	23-%"	30-%"	22-5/16"	29-5/16"	8-11/16"	44	Two each of:
C4026	1-¼" square	✓	20"	27"	7-34"	23-%"	30-%"	22-5/16"	29-5/16"	7-11/16"	44	Cosmic, Galaxy (FE20C) (mount 20 lb to tub)
C4027	2-½" rolled	✓	20"	27"	7-¾"	23-%"	30-%"	22-5/16"	29-5/16"	7-1/16"	45	Mercury 2.5 - 15.5 lb
C4022	4" rolled w/ rec hndl	✓	20"	27"	7-¾"	23-%"	30-¾"	22-5/16"	29-5/16"	5-¾"	46	Sentinel 5 lb Grenadier
C4028	4-½" rolled		20"	27"	7-3/4"	23-%"	30-%"	22-5/16"	29-5/16"	5-1/16"	47	Saturn

Fire-rated specific wall opening

*Confirm wall rough opening depth prior to ordering








© 2025 Activar Construction Products Group, Inc.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION IS PROHIBITED. Page 2 of 3

ebuildingproducts.com

FIRE PROTECTION CABINET - ARCHITECTURAL: ACADEMY FIRE-FX2™ SERIES - Aluminum



DOOR/LATCH STYLE

GLAZING/DOOR TYPE

	MODEL	DESCRIPTION	MODEL	DESCRIPTION
	F	Full view	10	.09" Clear acrylic
	G	Full view w/ Saf-T-Lok™	13	1/4" Clear wired glass
	D	Horizontal duo	15	1/8" Bronze acrylic
	E	Horizontal duo w/ Saf-T-Lok™	16	1/8" Gray acrylic
	V	Vertical duo	17	1/8" Clear tempered glass
	W	Vertical duo w/ Saf-T-Lok™	18	1/4" Clear safety glass
	В	Small view window w/ Saf-T-Lok™	21	No glazing, no lock w/ pull (S21 only)
	S	Solid (no glazing)	22	No glazing, Saf-T-Lok™ w/ pull (L22 only)
	L	Solid (no glazing) w/ Saf-T-Lok™	24	No glazing, Saf-T-Lok™ and no pull (L24 only)

OPTIONS HANDLE/LATCH (installed at an additional cost)

ALARM OPTIONS

(installed at an additional cost)

MODEL	DESCRIPTION	MODEL	DESCRIPTION
Α	Recessed handle	CA	Commander
LH	Lever handle (not avail. with Saf-T-Lok™)	BA	Brigadier
MC	Magnetic latch (replaces roller catch)	SA	Strobe

FINISH OPTIONS

CUSTOM LETTERING OPTIONS (when manufactured at additional cost)

MODEL	DESCRIPTION		MODEL	DESCRIPTION
BK	Black door, trim, tub		SS	Silkscreen
R	Red door, trim, tub		ET	Etching on glass
COLOR - OTHER (please specify)			EN	Engraving on metal
Door			LETT	ERING - OTHER (please specify)
Trim			Other	
Tub		Refe	er to supple	emental submittal for more options

Refer to supplemental submittal for more options

HANDLE/LATCH OPTIONS (sold separately)

QTY MODEL DESCRIPTION PUF Futura "FIRE" Mill PUFR Futura "FIRE" Red PUFW Futura "FIRE" White PUCH Chrome pull handle

PLASTIC SIGNS (sold separately)

·							
QTY	MODEL	DESCRIPTION					
	225	FE, 3D ANGLE, 4" x 12"					
	235	FE, 3D TENT, 4" x 18"					
	245	FE, 3D TENT, 5" x 6"					
	255	FE, FLUSH, 4" x 12"					

I ETTERING (sold senarately)

	LETTERING (Sold Separately)							
QTY	MODEL	FIRE EXTINGUISHER" DESCRIPTION						
	LDCVRFE	DIE CUT, VERT, RED, 3/4" x 18"						
	LDCVWFE	DIE CUT, VERT, WHITE, 3/4" x 18"						
	LDCVBFE	DIE CUT, VERT, BLACK, 3/4" x 18"						
	LDVRFE	DECAL, VERT, RED, 3/4" x 18"						
	LDVBFE	DECAL, VERT, BLACK, 3/4" x 18"						
	LDVWFE	DECAL, VERT, WHITE, 3/4" x 18"						
	LDCVRFE-ESM-A	DIE CUT, VERT, RED, (fits 81 tub), 3/4" x 14"						
	LDCHRFE-2	DIE CUT, HORZ, RED, 2" HIGH, 4-1/2" x 21"						
	Other							

Refer to supplemental submittal for more options

Refer to supplemental submittals for information on more options and accessories.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.

