# ebuildingproducts.com

2022


## **Stucco and Plaster**


Section: 09200


#### Continuous Soffit Vent "F" Series 2-3/8", 3", 4" and 6" vents

Number	Ground	Vent Area	Air Flow/linear ft.	Pieces per Box
F549-50	1/2" (13 mm)	2-3/8" (60 mm)	15 sq. in. (9,678 sq. mm)	13
F549-58	5/8" (16 mm)	2-3/8" (60 mm)	15 sq. in. (9,678 sq. mm)	13
F549-75	3/4" (19 mm)	2-3/8" (60 mm)	15 sq. in. (9,678 sq. mm)	13
F549-78	7/8" (22 mm)	2-3/8" (60 mm)	15 sq. in. (9,678 sq. mm)	13
F3549-50	1/2" (13 mm)	3" (76 mm)	15 sq. in. (9,678 sq. mm)	13
F3549-58	5/8" (16 mm)	3" (76 mm)	15 sq. in. (9,678 sq. mm)	13
F3549-75	3/4" (19 mm)	3" (76 mm)	15 sq. in. (9,678 sq. mm)	13
F3549-78	7/8" (22 mm)	3" (76 mm)	15 sq. in. (9,678 sq. mm)	13
F4549-50	1/2" (13 mm)	4" (102 mm)	16 sq. in. (10,323 sq. mm)	13
F4549-58	5/8" (16 mm)	4" (102 mm)	16 sq. in. (10,323 sq. mm)	13
F4549-75	3/4" (19 mm)	4" (102 mm)	16 sq. in. (10,323 sq. mm)	13
F4549-78	7/8" (22 mm)	4" (102 mm)	16 sq. in. (10,323 sq. mm)	13
F6549-50	1/2" (13 mm)	6" (152 mm)	18 sq. in. (11,614 sq. mm)	10
F6549-75	3/4" (19 mm	6" (152 mm)	18 sq. in. (11,614 sq. mm)	10









7" (178 mm)

> 6" (152 mm)

° ° °

F6549

1" (25 mm)

### Connector Clips Included Application:

Allows for installation against wall or fascia board areas of soffit. Vent holes 1/8" (3 mm) diameter. Connector clips included. Contact customer service for price, availability and delivery information.

#### **Specifications:**

Soffit Vent shall be Plastic Components Inc. #\_\_\_\_\_. All exterior accessories shall be of PVC material conforming to ASTM standards D1784, C1063, C1861 and D4216. They shall be used where specified by the design authority and installed per industry standards







855-832-8453