



Continuous Soffit Vent for Fiber Cement Board Submittal Sheet



STOCK NO.	A SIZE	B SIZE	AIRFLOW/ LF	LENGTH	PCS. PER BOX
300X08	2 5/8"	3 3/4"	15 sq in.	8'	50
300X10	2 5/8"	3 3/4"	15 sq in.	10'	50
301X08	1 3/4"	3 1/4"	7 sq in.	8'	50
301X10	1 3/4"	3 1/4"	7 sq in.	10'	50
3300X08	3"	4 1/2"	15 sq in.	8'	35
3300X10	3"	4 1/2"	15 sq in.	10'	35
4300X10	4"	5 1/2"	16 sq in.	10'	35
4300X08	4"	5 1/2"	16 sq in.	8'	35
6300	6"	7"	20 sq in.	10'	30

Description: The Continuous Soffit Vent for Fiber Cement Board offers a clean, easy solution for venting soffit areas without breaking the budget. The wide flange makes installation simple, and it's made from tough, exterior-grade PVC that won't rust or corrode. Great paint adhesion and solid stucco bonding help maintain a crisp, finished look season after season.

Advantages: Made from exterior grade PVC. Provides a high impact resistant, rust-proof termination corner.


Applicable Standards: Rigid exterior grade PVC products made by Trim-Tex meet ASTM specifications C926, C1063, C1780, C1861, D1784 and D4216.

Installation: Trim-Tex recommends following established acceptable industry standard installation methods. All butt joints, intersections, and ends should be caulked at the time of installation using elastomeric sealant. When painting Trim-Tex Exterior products, please refer to our painting resources to ensure proper performance and prevent product defects such as warping, oil canning, and buckling.

Job Name _____

Contractor _____

Date _____



Approvals (Signatures or Stamps)