



2601 Spenwick Dr  
Houston, TX 77055

ph: 713-263-8001  
fax: 713-263-7577

May 9, 2012

RE: Metacaulk® Firestopping Materials  
LEED® Product Information

TO: Whom It May Concern

This letter will detail the contribution of Metacaulk® firestopping materials to the LEED Green Building Rating System in accordance with LEED-NC, CS, CI and School Rating Systems.

**MR Credit 2.1: Construction Waste Management, Divert 50% form Disposal**

**MR Credit 2.2: Construction Waste Management, Divert 75% from Disposal**

In areas where facilities exist, the following Metacaulk® materials are recyclable and can contribute to earning Materials and Resources Credit 2.1 or Credit 2.2.

• Carton	Cardboard	2 lbs / carton
• 10.3 oz caulk tube	HDPE	40 g. / tube
• 20.2 oz foil pack	Mylar	5 g. / pack
• 30 oz caulk tube	HDPE	98 g. / tube
• quart bottle	HDPE	57 g. / bottle
• 5 gallon pail	HDPE	934 g. / pail
• Wooden pallet	wood	45 lbs. / pallet

**MR Credit 5.1: Regional Materials, 10% Extracted, Processed & Manufactured Regionally**

**MR Credit 5.2: Regional Materials, 20% Extracted, Processed & Manufactured Regionally**

Metacaulk® firestopping materials are manufactured in one location Houston, Texas. If these locations fall within a 500-mile radius of the project site and the location the raw materials used to make the finished product are extracted, recovered or harvested within a 500-mile radius of the project, then these materials or a portion of the materials can contribute to earning Materials and Resources Credit 5.1 and Credit 5.2.

The following are the locations of the Metacaulk® firestopping materials manufacturing plants:

<u>Metacaulk® Product</u>	<u>Location</u>
All Metacaulk® Products	Houston, Texas

Please contact your local Metacaulk® Representative to request a project specific letter pertaining to Credit 5.1 and Credit 5.2. The letter will provide the location where the raw materials are extracted, recovered or harvested in relation to the location of the project.

**EQ Credit 4.1: Low Emitting Materials, Adhesives & Sealants**

**EQ Credit 4.2: Low Emitting Materials, Paints & Coatings**

The volatile organic content (VOC) of Metacaulk® firestopping materials is listed below for those products that are lower than the minimum LEED requirements for low-emitting materials. These materials can help contribute to earning Indoor Environmental Quality EQ Credit 4.1 and 4.2.

<u>Metacaulk Product</u>	<u>EQ Credit</u>	<u>VOC Content (g/l)</u>
Metacaulk® 1000	4.1	10
Metacaulk® 950	4.1	10
Metacaulk® 835+	4.1	10
Metacaulk® MC 150+	4.1	10
Metacaulk® 350i	4.1	10
Metacaulk® Putty pads & Sticks	4.1	10
Metacaulk® 1100	4.2	10
Metacaulk® 1200	4.2	10
Metacaulk® Joint Strip	4.1	10
Metacaulk® Wrap Strip	4.1	10
Metacaulk® 1500	4.1	10
Metacaulk® Industrial Cable Coating	4.2	10

Please feel free to contact me with any additional questions or information.

Sincerely,



Terry Gossett  
Technical Service