ebuildingproducts.com



FIRE EXTINGUISHERS - NEBULA WATER MIST - Portable Handheld

All water mist extinguishers are of non-magnetic construction, and are third party tested to be safe to use in proximity to MRI equipment. They are ideal for extinguishing live electrical fires because the mist is non-conductive, and does not leave a chemical residue.





CLASS A FIRES CLASS C FIRES

Common Combustibles Energized Electrical Equipment

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

Qty.	Model	Туре	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 🕕	Optional Mounting Bracket	Tesla Rating	USCG Approved
	Nebula 270 (FE270A)		1-¾ gal	7 lbs. «	7″	24-1⁄2″	11″	1.1 cu. ft.	2A:C	MB810NM	Up to 11.7	
	Nebula 272 (FE272A)	Water Mist	2-½ gal	8 lbs. «	7″	27-1⁄2″	11″	1.3 cu ft.	2A:C	MB810NM	Up to 11.7	
	Nebula 250 (FWM250C)	Wilse	2-½ gal	8.3 lbs.«	7″	28″	14″	1.3 cu ft.	2A:C		Up to 3	

Non-magnetic J Hook wall bracket standard - Mounting bracket available at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

«The Nebula Extinguishers are shipped empty.

	800-554-6077	Distributor:		Project:			
	sales@activarcpg.com	Contractor:		Approved By:			
	www.activarcpg.com	Date:		Architect:			
9702 Newton Ave S. Bloomington, MN 55431 Ma	ny Locations Across North America	Scale: N/A	Pages: 1 of 1	Item #:			
© 2021 Activar Construction Products Group, Inc. THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.							

2 2021 Activar Construction Products Group, Inc. any repropution vantage of a start of the writement permission of activar construction products group, Inc.

SPECIFICATIONS:

The water mist extinguisher is ideal for Class A fires where a potential Class C (electrical) hazard exists. Units shipped empty.

Conforms to Test Standards: CAN/ULC-S554-ANSI/UL8 & CAN/ULC-S508-ANSI/UL711

Operation: The unique misting nozzle provides safety from electrical shock, making this extinguisher ideal for use in telecommunications and cleanroom environments.

Temperature Range: 40° F (4° C) to 120° F (49° C) **Construction:** Non-magnetic stainless steel cylinder and misting nozzle. For use in medical facilities.