ebuildingproducts.com

FIRE EXTINGUISHERS - Orbit Multi-Purpose Dry Chemical & Purple K - Portable Handheld

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail.

Not recommended for use on sensitive electronic equipment.







CLASS A FIRES

Common Combustibles



Flammable Liquids

Flammable Liquid and Gases



CLASS C FIRE

Energized Electrical Equipment





Button Hook for FE10V & FPK10VB

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

SPECIFICATIONS:

The Orbit Fire Extinguisher is as much as 40 percent slimmer than traditional 10-lb. models, allowing for more efficient and elegant building design. It is the only 10-lb. fire extinguisher that is always compliant with ADA protruding object regulations and local building codes.

ABC Dry Chemical

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

Purple K

Contain specially fluidized and siliconized potassium bicarbonate dry chemical which is particularly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K is the preferred fire fighting agent of oil, gas, chemical and utilities industries

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation. Approved to -40°F (-40°C) - 120° F (49°C)

Construction: Corrosion-resistant tempered aluminum vessel with aluminum valve and siphon tube. Also features visual pressure gauge, stainless steel pull pin, handles, bracket and button hook. Durable powder coat finish.

Valve Material: Aluminum

Options	Available Models			
Non-Magnetic	FE10V*, FE10VB*			

*Tested to 3 Tesla

Qt	lty. Model	Туре	Nominal Capacity	Shipping Weight	Cylinder Dia. In Inches	Overall Height In Inches	Overall Width In Inches	Shipping Vol. Approx.	UL Rating (I)	Mounting	USCG Approved
	FE10V	ABC Dry	10 lbs.	28.5 lbs.	3	22	11	1.35 cu.ft.	4-A:80-B:C	Surface or 3.25" Depth Cabinet	
	FE10VB	Chemical	10 lbs.	26.5 lb	3.5	23	9	1.35 cu.ft.	4-A:80-B:C	Surface	
	FPK10VB	Purple K	10 lbs.	9.25lbs.	3.5	23	9	1.35 cu.ft.	80-B:C	Surface	

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.





Distributor:		Project:		
Contractor:		Approved By:		
Date:		Architect:		
Scale: N/A	Pages: 1 of	Item #:		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. ANY REPRODUCTION IN PART OR A 5 A WHILE WRITTEN DEBNICSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED. REV. A - MA				

© 2019 Activar Construction Products Group, Inc.

info@ebuildingproducts.com