

FIRE EXTINGUISHERS - SENTINEL CARBON DIOXIDE - C - Portable Handheld

Carbon dioxide is a trusted non-conductive clean agent that is more effective for dealing with electronic equipment fires. Typically used in offices, classrooms, retail and research facilities.



CLASS B FIRES
Flammable Liquids and Gases



CLASS C FIRES
Energized Electrical Equipment

SPECIFICATIONS:

This extinguisher contains liquid carbon dioxide under pressure.

Conforms to Test Standards: CAN/ULC-S503, ANSI/UL154 & CAN/ULC-S508-ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the carbon dioxide to be forced out. The discharge, which changes into a gas and appears as a smothering cloud of white snow, is then directed to the fire through a funnel-shaped horn. Electrically non-conductive.

Temperature Range: -22° F (-30° C) to 120° F (49° C)

Construction: Lightweight, high-pressure, aluminum cylinder with O-ring seal and straight thread brass valve. The Sentinel is absolutely rust-free and up to 30% lighter than CO2 units with steel cylinders.

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA 10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating	Optional Mounting Bracket	USCG Approved
	Sentinel 5 (FS05C)	Carbon Dioxide	5 lbs.	13-3/4 lbs.	5-1/4"	17-3/4"	8-1/4"	.65 cu.ft.	5B:C	MB809C	YES
	Sentinel 10 (FS10C)		10 lbs.	27-3/4 lbs.	7"	19-3/4"	12"	1.3 cu.ft.	10B:C	MB810C	YES
	Sentinel 15 (FS15C)		15 lbs.	37-3/4 lbs.	7"	26-3/8"	12"	1.0 cu.ft.	10B:C	MB810C	YES
	Sentinel 20 (FS20C)		20 lbs.	49 lbs.	8"	26-7/8"	13"	2.1 cu.ft.	10B:C	MB811C	YES

J Hook wall bracket standard - Mounting bracket available at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Across North America

800-554-6077
sales@activarcpg.com
www.activarcpg.com

Distributor:		Project:	
Contractor:		Approved By:	
Date:		Architect:	
Scale: N/A	Pages: 1 of 1	Item #:	