



ARVB

VALVE BOXES

Recessed

Application

- Provides easy access to all types of valves and controls that need to be concealed in the wall, but protected by a fully enclosed box

Product Features

- The depth of the valve box can be modified to meet all the valve and control requirements
- When required, vision panels, louvers, engrave plates can be supplied, along with special holes for pipes or conduits

ARVB Valve Box Specifications:

Material: Stainless Steel or Steel: 16 gauge door, frame, box

Door: 16 gauge, flush to frame — rounded safety corners

Frame: 16 gauge, one piece outer flange welded to box

Box: 16 gauge, fully enclosed, completely attached to frame.

When required box can be made with open back.

Hinge: Continuous, concealed

Latch: Cylinder lock & key, Also available: Slotted Screwdriver

Cam Latch, spanner head cam latch, flush paddle handle, thumb turn latch.

Finish: Stainless Steel: Type 304 - #4 satin polish. Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baked enamel

ARVB STANDARD SIZES

(other sizes available upon request)

| Nominal Door Size W&H | | Opening | Weight per Door | |
|-----------------------|-----------------|---------|-----------------|-----|
| Inches | mm | | lbs. | kg. |
| 8 x 8 x 4 | 203 x 203 x 102 | 1 | 5.9 | 2.7 |
| 8 x 8 x 6 | 203 x 203 x 152 | 1 | 6.8 | 3.1 |
| 8 x 8 x 8 | 203 x 203 x 203 | 1 | 8.0 | 3.6 |
| 12 x 12 x 4 | 305 x 305 x 102 | 1 | 9.9 | 4.5 |
| 12 x 12 x 6 | 305 x 305 x 152 | 1 | 11.5 | 5.2 |
| 12 x 12 x 8 | 305 x 305 x 203 | 1 | 13.2 | 6.0 |

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

