



# AT-5020

## SPECIALTY DOORS

### Recessed Access Door

#### Application

- For flush installation in walls or ceilings when it is required to conceal the door panel

#### Product Features

- Door is recessed 1"

#### AT-5020 Access Door Specifications:

**Material:** Steel

**Door:** 16 gauge, Recessed 1"

**Mounting Frame:** 14 gauge

**Hinge:** Concealed, pivoting rod type, for wall applications over 24"x24" we supply a concealed pin hinge

**Standard Latch:** Flush to surface, Slotted Screwdriver Cam Latch

**Optional Latches/Locks:** Cylinder lock and key, allen head cam latch, spanner head cam latch

**Finish:** Steel: 5-stage iron phosphate preparation with prime coat of White alkyd baked-on enamel



#### AT-5020 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 X 12	305 X 305	1	5.9	2.7
18 X 18	457 X 457	2	10.8	4.9
24 X 24	610 X 610	2	21.0	9.5
24 X 36	610 X 914	2	30.0	13.6

Wall or ceiling opening is nominal door size + 3/8" (9 mm)  
For detailed specifications see submittal sheet

