



# FB-5060

## FIRE-RATED UNINSULATED

### Application

- For wall applications.
- Designed to maintain continuity in a 2 hour fire rated wall, when temperature is not a factor

### Product Features

- Concealed hinge • Self-closing • Self-Latching
- Inside latch release
- Available with a removable door panel

### FB-5060 Access Door Specifications:

**Door / Door Frame:** Steel or Stainless Steel: 16 gauge door, 16 gauge mounting frame. Flush to frame with reinforced edges, flange to be 1" wide

**Hinge:** Concealed

**Fire Rating (Walls):** UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. (optional)  
Max sizes 36 x 48 and 24" x 79"

**Standard Latch:** Universal self-latching bolt, operated by either a knurled knob or flush key. When master keying is required, doors can be prepared for rim or mortise cylinder locks.

**Finish:** Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baked-on enamel. Stainless Steel: #4 satin polish.



### FB-5060 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
8 X 8	203 X 203	1	5.5	2.5
10 X 10	254 X 254	1	6.5	2.9
12 X 12	305 X 305	1	8.3	3.7
14 X 14	356 X 356	1	8.3	3.8
16 X 16	406 X 406	1	11.1	5.0
18 X 18	457 X 457	1	13.8	6.3
22 X 30	559 X 762	2	24.9	11.3
22 X 36	559 X 914	2	27.5	12.5
24 X 24	610 X 610	1	20.1	9.1
24 X 30	610 X 762	2	25.6	11.6
24 X 36	610 X 914	2	29.7	13.5
24 X 48	610 X 1219	2	35.7	16.2
30 X 30	762 X 762	2	28.4	12.9
36 X 36	914 X 914	2	38.7	17.6
36 X 48	914 X 1220	2	48.8	22.1

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

This document contains proprietary information which is the property of Acudor Products. It shall not be modified, copied, furnished, nor distributed (in whole or in part) without proper authorization. Copyright © 2020 Acudor Products.

