



FWC-5015

Fire Rated Access Door, Recessed for Drywall Ceilings

Application

- For installation in drywall ceilings requiring concealing of the door panel consistent to surroundings
- For use in Fire Rated Ceilings that needs tested and certified doors having Fire Resistance Rating of 90 minutes.

Product Features

- Recessed reinforced insulated door fitted with 5/8" Fire-rated drywall.
- Concealed hinge & self-centering device ensures seamless appearance in ceiling
- Self-closing & self-latching door mechanism
- Perforated Frame ensures trouble-free application of skim coat to edge of the door
- Zinc coated steel provides superior corrosion resistance
- Testing Standards – CAN ULC S101-14, ASTM E119-16 and NFPA 251

FWC-5015 Access Door Specifications:

Door: Steel-22 Gauge recessed fitted with 5/8" thick drywal suitable to accept skim coat finish on site.

Door Frame: Steel-22 Gauge press bent for strength and rigidity with pre-punched flanges for convenient mounting and accepting skim coat finish on site

Hinge: Concealed

Fire Rating (Ceilings): Meets 90 minutes Fire Resistance Rating in accordance with CAN ULC S101-14, ASTM E119-16 and NFPA 251

Latch: Self-latching bolt, operated by flush key

Finish: Satin coat steel

FWC-5015 STANDARD SIZES

(other sizes available upon request)

| Nominal Door Size W&H | | Latches | Weight per Door | |
|-----------------------|-----------|---------|-----------------|------|
| Inches | mm | | lbs. | kg. |
| 12 X 12 | 305 X 305 | 1 | 10 | 4.5 |
| 16 X 16 | 406 X 406 | 1 | 16 | 7.3 |
| 18 X 18 | 457 X 457 | 1 | 20 | 9.1 |
| 24 X 24 | 610 X 610 | 1 | 31 | 14.1 |
| 24 X 36 | 610 X 914 | 2 | 46 | 20.9 |

Ceiling opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet
PATENT PENDING



Drywall insert included

PATENT PENDING

