ebuildingproducts.com

D - Horizontal duo

panel with pull E - Horizontal duo

panel with pull and Saf

F - Full glass with pull

G - Full glass with pull handle and Saf-T-Lok

Date:

SUBMITTAL: CROWNLINE™ FIRE-FX2™ CABINETS - STAINLESS STEEL

PG 1 OF 2

V - Vertical due nanel

W - Vertical duo pane

with pull and Saf-T-Lok

Fire-Rated Crownline Cabinets Provide A Wide Selection of Door Styles, Glazing and Sizes. These Durable Cabinets are Designed to Industry Standards for Fire Department Valves, Fire Hose Rack Units and Extinguishers.

Door & Trim: #4 Brushed finish stainless steel. 1-3/4" Trim on face and door. These flush cabinet doors are mounted in a 5/8" door stop, are attached by a continuous hinge and are equipped with zinc-plated handle and roller catch for all non-locking doors. Theft-deterrent SAF-T-LOK™ also available

Trim Style and Depth: 1-3/4" face trim on frame and 1-1/4" trim on door. Recessed - 3/8" flat trim, Semi-recessed - 1-1/4" Square Edge or 2-1/2" Rolled Edge. All models meet ADA 4" projection requirement. See separate submittal for trimless models.

Tub: The tub is constructed of cold rolled steel with white powder-coat finish standard. Tub forms a flange to cover cut edges of wallboard material. Fire-resistant material is attached to the exterior of the tub.

Knockouts: Knockouts are not provided on Fire-Rated Cabinets. Instructions for Knockouts in the field are provided and must be strictly adhered to, to maintain fire rating.

Fire Rating: Fire-FX2TM cabinets are UL listed and labeled as an approved membrane penetration firestop system for up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/ULC-S115, when properly installed in a wall assembly according to installation instructions.

STEP 1: SELECT MODEL NUMBER, TRIM & QUANTITY (Refer to Chart on Page 2)

STEP 2: SELECT DOOR STYLE (Check one box below) Full Glazing L22 Solid with SAF-T-LOK S21 - Solid with pull B10 - Acrylic view A - Center duo panel L22 - Solid with pull and Saf-T-Lok L24 - Solid with cylin-G Full Glazing with SAF-T-LOK Vertical Duo vindow with pull, and Saf-T-Lok Horizontal Duo Panel W Vertical Duo with SAF-T-LOK Horizontal Duo Panel with SAF-T-LOK B10 Acrylic View Window with SAF-T-LOK Center Duo Panel with SAF-T-LOK L24 Solid with Cylinder Lock & No Handle FIRE-FX2 CABINET WITH NEW LIGHTWEIGHT INSULATION S21 Solid Door View Door Styles Online 3/16" Typic STEP 3: SELECT DOOR GLAZING (Check one box below) Attach to Wall 10 Clear Acrylic 16 Gray Acrylic 13 Clear Wire Glass with Wire Glass 17 Clear Tempered Glass 15 Bronze Acrylic 18 Laminated Safety Glass STEP 4: OPTIONAL FEATURES AT ADDITIONAL COST: TYPICAL INSTALLATION #6 Matte Finish Stainless Steel **PUCH** Polished Chrome Pull Black Vertical FE Letters LDCVBFE #7 Polished Stainless Steel FDVO Decal Fire Department Valve Octagonal 6 x 6" Red Vertical FE Letters LDCVRFE #8 Mirror Finish Stainless Steel 1403 Decal Fire Hose Black/Red Horiz. Letters 4 x 9 White Vertical FE Letters LDCVWFE #4 Finish Stainless Tub LDCHRFDV-R Diecut Fire Dept. Valve Horiz.10-1/4 x 4-3/8 Black Horizontal FE Letters LDCHBFE Optional Tub Color: Black Red LDCVRFDV Diecut Fire Dept Valve Vert. 3/4" x 211/2" Red Horizontal FE Letters LDCHRFE **CA** Commander Alarm LDCVRFDV-R Diecut Fire Dept Valve Vert. Rever. 3/4" x 211/2" White Horizontal FE Letters LDCHWFE BA Brigadier Alarm LDCHRFDV Diecut Fire Department Valve Ascend. 1" x 17" Lettering: Etched on Glass, Engraving on Futura "Fire" Handle__Mill__Red__White LDCVRFSCV-R Diecut Fire Sprinkler Cont. Valve Vert 3/4" x 18" Metal, Silkscreen; Not Available for #7 or #8 Finish on Doors. Check Box and Attach PRH Recessed Pull Handle Fire Hose Racks - See Separate Submittal Separate Submittal to Order. Shelf for 8000 Series—12" from Top It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances. Distributor: Quantity: JL INDUSTRIES Contractor: Approved By: Model #: Architect:


Project:


12/22/2023

©2023 ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC.

ebuildingproducts.com

SUBMITTAL:CROWNLINE FIRE-FX2™ VALVE & HOSE CABINETS - STAINLESS STEEL PG 2 OF 2





3/8" (.9cm) FLAT TRIM 1-1/4" (3.8cm) SQUARE TRIM 2-1/2" (6.4cm) ROLLED EDGE

TRIM & DOOR		TUB I.D. W x H x D					RECESSED WALL			RECOMMENDED HOSE RACK,
MATERIAL & SERIES		in Inches			FRAME O.D.		OPENING DIMS.			FIRE DEPARTMENT VALVES &
QTY #	TRIM STYLE	Α	В	С	Е	F	Width	Height	Depth	EXTINGUISHERS
Cabinets with Hose Rack & Extinguisher or Fire Department Valve										
6035	FLAT TRIM 3/8"	24	30	6	27 3/8	33 3/8	26 5/16	32 5/16	6 15/16	HOSE RACK: 1- 1/2" x 1-1/2" Hose Rack Unit with 50
6036	1-1/4" SQUARE EDGE	24	30	6	27 3/8	33 3/8	26 5/16	32 5/16	5 15/16	or 75' Hose (HRA:050B, 050CH, 075B, 075CH)
6037	2-1/2" ROLLED EDGE	24	30	6	27 3/8	33 3/8	26 5/16	32 5/16	4 11/16	& Cosmic 2½ or Galaxy 2½- 5 lb Extinguisher
6235	FLAT TRIM 3/8"	24	34 3/4	6	27 3/8	38 1/8	26 5/16	37 1/16	6 15/16	HOSE RACK: 1- 1/2" x 1-1/2" Hose Rack Unit - 100'
6236		24	34 3/4	6	27 3/8	38 1/8	26 5/16	37 1/16	5 15/16	Hose (HRA 100B, HRA100CH)
6237	2-1/2" ROLLED EDGE	24	34 3/4	6	27 3/8	38 1/8	26 5/16	37 1/16	4 11/16	& Cosmic 2½ or Galaxy 2½- 5 lb Extinguisher
6135	FLAT TRIM 3/8"	24	30	8	27 3/8	33 3/8	26 5/16	32 5/16	8 15/16	HOSE RACK:
6136		24	30	8	27 3/8	33 3/8	26 5/16	32 5/16	7 15/16	2-1/2" x 1-1/2" Hose Rack Unit
6137	2-1/2" ROLLED EDGE	24	30	8	27 3/8	33 3/8	26 5/16	32 5/16	6 11/16	50 or 75' Hose (HRA050B-2.5, HRA075B-2.5)
6435	FLAT TRIM 3/8"	24	34 3/4	8	27 3/8	38 1/8	26 5/16	37 1/16	8 15/16	HOSE RACK:
6436	1-1/4" SQUARE EDGE	24	34 3/4	8	27 3/8	38 1/8	26 5/16	37 1/16	7 15/16	2-1/2" x 1-1/2" Hose
6437	2-1/2" ROLLED EDGE	24	34 3/4	8	27 3/8	38 1/8	_	37 1/16	6 11/16	Rack Unit 100' Hose (HRA100B-2.5)
6635	FLAT TRIM 3/8"	24	38 3/4	8	27 3/8	42 1/8		41 1/16	8 15/16	HOSE RACK:
6636	1-1/4" SQUARE EDGE	24	38 3/4	8	27 3/8	42 1/8	26 5/16	41 1/16	7 15/16	2-1/2" x 1-1/2" Hose
6637	2-1/2" ROLLED EDGE	24	38 3/4	8	27 3/8	42 1/8	26 5/16	41 1/16	6 11/16	Rack Unit 125' Hose (HRA125B-2.5)
6335	FLAT TRIM 3/8"	30	30	8	33 3/8	33 3/8	32 5/16	32 5/16	8 15/16	HOSE RACK & FD VALVE OR EXTINGUISHER:
6336	1-1/4" SQUARE EDGE	30	30	8	33 3/8	33 3/8	32 5/16	32 5/16	7 15/16	1-1/2" OR 2-1/2" Valve; 50' or 75' Hose Rack Unit
6337	2-1/2" ROLLED EDGE	30	30	8	33 3/8	33 3/8	32 5/16	32 5/16	6 11/16	Plus FD Valve or Cosmic or Galaxy Fire Extinguisher
6535	FLAT TRIM 3/8"	32 3/4	34 3/4	8	36 1/8	38 1/8	35 1/16	37 1/16	8 15/16	HOSE RACK & FD VALVE OR EXTINGUISHER:
6536	1-1/4" SQUARE EDGE	32 3/4	34 3/4	8	36 1/8	38 1/8	35 1/16	37 1/16	7 15/16	1-1/2" OR 2-1/2" Valve, 100' Hose Rack Unit
6537	2-1/2" ROLLED EDGE	32 3/4	34 3/4	8	36 1/8	38 1/8	35 1/16	37 1/16	6 11/16	Plus FD Valve or Cosmic or Galaxy Fire Extinguisher
7235	FLAT TRIM 3/8"	32 3/4	38 3/4	8	36 1/8	42 1/8	35 1/16	41 1/16	8 15/16	HOSE RACK & FD VALVE OR EXTINGUISHER:
7236	1-1/4" SQUARE EDGE	32 3/4	38 3/4	8	36 1/8	42 1/8	35 1/16	41 1/16	7 15/16	1-1/2" OR 2-1/2" Valve,125' Hose Rack Unit
7237	2-1/2" ROLLED EDGE	32 3/4	38 3/4	8	36 1/8	42 1/8	35 1/16	41 1/16	6 11/16	Plus FD Valve or Cosmic or Galaxy Fire Extinguisher)
Cabinets for Fire Department Valves										
8535	FLAT TRIM 3/8"	18	18	8	21 3/8	21 3/8	20 5/16	20 5/16	8 15/16	
8536	1-1/4" SQUARE EDGE	18	18	8	21 3/8	21 3/8	20 5/16	20 5/16	7 15/16	FIRE DEPARTMENT VALVE:
8537	2-1/2" ROLLED EDGE	18	18	8	21 3/8	21 3/8	20 5/16	20 5/16	6 11/16	1-1/2" or 2-1/2"
8435	FLAT TRIM 3/8"	18	18	10	21 3/8	21 3/8	20 5/16	20 5/16	10 15/16	Fire Department Valve
8436	1-1/4" SQUARE EDGE	18	18	10	21 3/8	21 3/8	20 5/16	20 5/16	9 15/16	with Cap and Chain
8437	2-1/2" ROLLED EDGE	18	18	10	21 3/8	21 3/8	20 5/16	20 5/16	8 11/16	
8735	FLAT TRIM 3/8"	26	26	8	29 3/8	29 3/8	28 5/16	28 5/16	8 15/16	DUAL SIDE BY SIDE FIRE DEPARTMENT VALVE &
8736	1-1/4" SQUARE EDGE	26	26	8	29 3/8	29 3/8	28 5/16	28 5/16	7 15/16	EXTINGUISHER OR 2 FIRE DEPARTMENT
8737	2-1/2" ROLLED EDGE	26	26	8	29 3/8	29 3/8	28 5/16	28 5/16	6 11/16	VALVES:
8635	FLAT TRIM 3/8"	26	26	10	26 1/4	26 1/4	28 5/16	28 5/16	10 15/16	1-1/2" or 2-1/2" Fire Department Valve
8636	1-1/4" SQUARE EDGE	26	26	10	26 1/4	26 1/4		28 5/16	9 15/16	with Cap and Chain
8637	2-1/2" ROLLED EDGE	26	26	10	26 1/4	26 1/4	28 5/16	28 5/16	8 11/16	Plus Extinguisher - Cosmic & Galaxy 2½ to 10
8035	FLAT TRIM 3/8"	16	40	9	19 3/8	43 3/8	18 5/16	42 5/16	9 15/16	BUAL EVENOUED A ED VALVE CORNE
8036	1-1/4" SQUARE EDGE	16	40	9	19 3/8	43 3/8	18 5/16	42 5/16	8 15/16	DUAL EXTINGUISHER & FD VALVE CABINET:
8037	2-1/2" ROLLED EDGE	16	40	9	19 3/8	43 3/8	18 5/16	42 5/16	7 11/16	Cosmic or Galaxy Fire Extinguisher

ADA Cabinet Mounting Height: Standard Pull on G, E, W, L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or Doors with Recessed Pull are Centered on Door.