SUBMITTAL: CROWNLINE™ VALVE & HOSE CABINETS - ALUMINUM

PAGE 1 OF 2

Crownline Cabinets Provide A Wide Selection of Door Styles, Glazing and Sizes. These Durable Cabinets are Designed to Industry Standards for Fire Department Valves, Fire Hose Rack Units and Extinguishers.

Door & Trim: Clear anodized aluminum. 1-3/4" Trim on face and door. These flush cabinet doors are mounted in a 5/8" door stop, are attached by a continuous hinge and are equipped with zinc-plated handle and roller catch for all non-locking doors. Theft-deterrent SAF-T-LOK™ also available.

Trim Style and Depth: 1-3/4" face trim on frame and 1-1/4" trim on door. Recessed - 3/8" flat trim.

Semi-recessed - 1-1/4" Square Edge or 2-1/2" Rolled Edge. Rolled edge models are constructed of mechanically-joined extrusions (see photo).

Surface mounted - Square edge. See separate submittal for trimless.

Tub: CRS, white powder-coat finish standard. Surface-mounted tubs are of the same material as the door and trim

Knockouts: K.O's are provided on both sides of the cabinet. K.O.'s on left side will be located using "J" dimension, K.O.'s on right side using "K" dimension and may be

offset from K.O.'s on "J" side of cabinet. Models 6027 & 6227 - Specify knockout location. Provided on surface mounted cabinets by request except for rolled edge models. Custom location K.O.'s available. See page 2 for drawings of K.O. locations.

(Check one box below)

Vertical Duo

View Door Styles Online

(Check one box below)

17 Clear Tempered Glass

18 Laminated Safety Glass

16 Grav Acrylic

W

ADA Cabinet Mounting Height: Standard Pull on G, E, W, L22, A and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door

L22 Solid with SAF-T-LOK

Vertical Duo with SAF-T-LOK

B10 Acrylic View Window with SAF-T-LOK

L24 Solid with Cylinder Lock & No Handle

STEP 1: SELECT MODEL NUMBER, TRIM & QUANTITY (Refer to Chart on Page 2)

Fire-Rated Option Available: Yes - See separate submittal.

STEP 2: SELECT DOOR STYLE

Horizontal Duo Panel

STEP 3: SELECT DOOR GLAZING

13 Clear Wire Glass with Safety Film

Full Glazing with SAF-T-LOK™

A Center Duo Panel with SAF-T-LOK

Horizontal Duo Panel with SAF-T-LOK

Full Glazing

S21 Solid Door


10 Clear Acrylic


15 Bronze Acrylic



6225A10

2-1/2" Rolled Edge







F - Full glass with pull G - Full glass with pull handle and Saf-T-Lok (Not Shown)

D - Horizontal duo panel with pull E - Horizontal du panel with pull and Saf -T-Lok. (Not Shown)

V - Vertical duo panel with pull W - Vertical duo panel with pull and Saf-T-Lok. (Not

Shown)





S21 - Solid with pull L22 - Solid with pull and Saf-T-Lok 1 24 - Solid with cylin der key lock/no pull not shown)

Quantity:

Architect:

Date:

Approved By:

B10 - Acrylic view window with pull and Saf-T-Lok

A - Center duo panel with pull and Saf-T-Lok

ST	STEP 4: OPTIONAL FEATURES AT ADDITIONAL COST:									
	Dark Bronze Anodized Door & Trim		FDVO Decal Fire Department Valve Octagonal 6 x 6"							
	Aluminum Tub - Clear Anodized		1403 Decal Fire Hose Black/Red Horiz. Letters 4 x 9							
	Optional Tub Color: BlackRed		LDCHRFDV-R Diecut Fire Dept. Valve Horiz.10-1/4 x 4-3/8							
	Futura "Fire" HandleMillRedWhite		LDCVRFDV Diecut Fire Dept Valve Vert. 3/4"" x 211/2"							
	PRH Recessed Pull Handle		LDCVRFDV-R Diecut Fire Dept Valve Vert. Rever. 3/4" x 211/2"							
	PUCH Polished Chrome Handle		LDCHRFDV Diecut Fire Department Valve Ascend. 1" x 17"							
	SA Strobe Alarm (surface mount models)		LDCVRFSCV-R Diecut Fire Sprinkler Cont. Valve Vert ¾"x	18"						
	CA Commander Alarm		Shelf for 8000 Series—12" from Top							
	BA Brigadier Alarm		Fire Hose Racks - See separate submittal							
lt ic	the responsibility of the sustamer to communicate s	noc	ifications and product performance requirements that are peeded for the	oir ann						

-
Black Vertical FE Letters LDCVBFE
Red Vertical FE Letters LDCVRFE
White Vertical FE Letters LDCVWFE
Black Horizontal FE Letters LDCHBFE
Red Horizontal FE Letters LDCHRFE
White Horizontal FE Letters LDCHWFE
Engraving or Silkscreen on Door (Except
Dark Bronze Anodized), Etching or Silk-

screen on Glass. Check Box & Attach Separate Submittal

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.



IL INDUSTRIES


Distributor: Contractor: Model #:

Project:


12/22/2023

ebuildingproducts.com

SUBMITTAL: CROWNLINE VALVE & HOSE CABINETS - ALUMINUM



 Cabinets that meet ADA projection requirement



PAGE 2 OF 2

ADA Cabinet Mounting Height: Standard Pull on G, E, W, A,L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door.

8	1	Standard on Alum. & Steel												
	13 1								1=0=0	307AM	03/03/04/30/06/04/	~~	~	
		RIM & DOOR		I.D. W x H	x D	FRAM	IE O.D.	RECESSED WALL OPENING				OCK		RECOMMENDED HOSE RACK,
		ERIAL & SERIES		in Inches	_		-				LOCATIONS			FD VALVES &
QTY	#	TRIM STYLE				E	F		Height		J		K	EXTINGUISHERS
		Cabinets with Hose Rack & Extinguisher of												
		FLAT TRIM 3/8" •	24	30	6	27 3/8	33 3/8	25	31	5 7/8	2 1/2	4	2 1/2	HOSE RACK:
	6026	1-1/4" SQUARE EDGE•	24	30	6	27 3/8	33 3/8	25	31	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit with 50 or 75' Hose (HRA:050B, 050CH, 075B,
	6027	2-1/2" ROLLED EDGE●	24	30	6	27 3/8	33 3/8	25	31	4 1/4			Ordering	075CH) & Cosmic 2½ or
	6023	SURFACE MOUNTED	27 3/16	33 3/16	6 1/2	27 3/8	33 3/8	-	-	-	Upon	Requ	ıest	Galaxy 2½- 5 lb Extinguisher
	6225	FLAT TRIM 3/8" •	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	5 7/8	2 1/2	4	2 1/2	HOSE RACK:
	6226	1-1/4" SQUARE EDGE•	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit - 100'
	6227	2-1/2" ROLLED EDGE•	24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	4 1/4	Specify \	When	Ordering	Hose (HRA 100B, HRA100CH) & Cosmic 2½ or Galaxy 2½- 5 lb Extinguisher
	6223	SURFACE MOUNTED	27 3/16	37 15/16	6 1/2	27 3/8	38 1/8	_	_	_	Uno	n Red	uest	
-		FLAT TRIM 3/8" •	24	30	8	27 3/8	33 3/8	25	31	7 7/8	4	4	2 1/2	
_	6126	1-1/4" SQUARE EDGE	24	30	8	27 3/8	33 3/8	25	31	6 7/8	4	4	2 1/2	HOSE RACK: 2-1/2" x 1-1/2" Hose Rack Unit
		2-1/2" ROLLED EDGE	24	30	8	27 3/8	33 3/8	25	31	6 1/4	4	4	2 1/2	50 or 75' Hose
		SURFACE MOUNTED	27 3/16	33 3/16	8 1/2	27 3/8	33 3/8	-	-	0 1/4		n Red		(HRA050B-2.5, HRA075B-2.5)
-		FLAT TRIM 3/8" •	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	7 7/8	4	4	2 1/2	(
	6426	1-1/4" SQUARE EDGE	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 7/8	4	4	2 1/2	HOSE RACK:
		2-1/2" ROLLED EDGE	24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 1/4	4	4	2 1/2	2-1/2" x 1-1/2" Hose
—		SURFACE MOUNTED	27 3/16	37 15/16	8 1/2	27 3/8	38 1/8	-	33 3/4	0 1/4		n Red		Rack Unit 100' Hose (HRA100B-2.5)
-		FLAT TRIM 3/8" •	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	7 7/8	4	4	2 1/2	
. —	6626	1-1/4" SQUARE EDGE	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 7/8	4	4	2 1/2	HOSE RACK:
—		2-1/2" ROLLED EDGE	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 1/4	4	4	2 1/2	2-1/2" x 1-1/2" Hose
	6623	SURFACE MOUNTED	27 3/16	41 15/16	8 1/2	27 3/8	42 1/8	-	J9 J/4 _	0 1/4		n Red		Rack Unit 125' Hose (HRA125B-2.5)
\vdash		FLAT TRIM 3/8" •	30	30	8	33 3/8	33 3/8	31	31	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE
′—	6326	1-1/4" SQUARE EDGE	30	30	8	33 3/8	33 3/8	31	31	6 7/8	4	4	2 1/2	OR EXTINGUISHER:
	6327	2-1/2" ROLLED EDGE	30	30	8	33 3/8	33 3/8	31	31	6 1/4	4	4	2 1/2	1-1/2" OR 2-1/2" Valve 50' or 75' Hose
-	+		33 3/16	33 3/16	8 1/2			-	-	0 1/4	Upon Request			Rack Unit Plus FD Valve Cosmic or
	6323	SURFACE MOUNTED				33 3/8	33 3/8			-		_		Galaxy Extinguisher
		FLAT TRIM 3/8" •	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE OR EXTINGUISHER:
-	6526	1-1/4" SQUARE EDGE•	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 7/8	4	4	2 1/2	1-1/2" OR 2-1/2" Valve, 100' Hose Rack
-	6527	2-1/2" ROLLED EDGE•	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 1/4	4	4	2 1/2	Unit Plus FD Valve or Cosmic or Galaxy
	6523	SURFACE MOUNTED	35 15/16	37 15/16	8 1/2	36 1/8	38 1/8	-	-	-		n Red		Extinguisher
		FLAT TRIM 3/8" ●	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE
	7226	1-1/4" SQUARE EDGE•	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	6 7/8	4	4	2 1/2	OR EXTINGUISHER: 1-1/2" OR 2-1/2" Valve, 125' Hose Rack
	7227	2-1/2" ROLLED EDGE•	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	6 1/4	4	4	2 1/2	Unit Plus FD Valve or Cosmic or Galaxy
	7223	SURFACE MOUNTED	35 15/16	41 15/16	8 1/2	36 1/8	42 1/8	-	-	-	Upo	Upon Request		Extinguisher
		Cabinets for Fire Department Valves												
		FLAT TRIM 3/8" ●	18	18	8	21 3/8	21 3/8	19	19	7 7/8	4	9	2 1/2	
	8526	1-1/4" SQUARE EDGE•	18	18	8	21 3/8	21 3/8	19	19	6 7/8	4	9	2 1/2	
-	8527	2-1/2" ROLLED EDGE•	18	18	8	21 3/8	21 3/8	19	19	6 1/4	4	9	2 1/2	FIRE DEPARTMENT VALVE:
-	8523	SURFACE MOUNTED FLAT TRIM 3/8" ●	21 3/16	21 3/16 18	8 1/2 10	21 3/8 21 3/8	21 3/8 21 3/8	- 19	- 19	9 7/8		n Red		1-1/2" or 2-1/2"
		1-1/4" SQUARE EDGE	18	18	10	21 3/8	21 3/8	19	19	8 7/8	5 5	9	5 5	Fire Department Valve with Cap and Chain
		2-1/2" ROLLED EDGE	18	18	10	21 3/8	21 3/8	19	19	8 1/4	5	9	5	Sup und Sham
		SURFACE MOUNTED	21 3/16		10 1/2	21 3/8	21 3/8	-	-	-		n Red		
		FLAT TRIM 3/8" •	26	26	8	29 3/8	29 3/8	27	27	7 7/8	4	13	2 1/2	
		1-1/4" SQUARE EDGE•	26	26	8	29 3/8	29 3/8	27	27	6 7/8	4	13	2 1/2	
		2-1/2" ROLLED EDGE	26	26	8	29 3/8	29 3/8	27	27	6 1/4	4	13	2 1/2	DUAL SIDE BY SIDE FIRE DEPART-
		SURFACE MOUNTED	29 3/16	29 3/16	8 1/2	29 3/8	29 3/8	-	-	-	Upo	n Red	uest	MENT VALVE & EXTINGUISHER OR 2
		FLAT TRIM 3/8" •	26	26	10	29 3/8	29 3/8	27	27	9 7/8	5	13	5	FIRE DEPARTMENT VALVES: 1-1/2" or 2-1/2" FD Valve w/Cap and Chain
	8626	1-1/4" SQUARE EDGE•	26	26	10	29 3/8	29 3/8	27	27	8 7/8	5	13	5	Plus Extinguisher - Cosmic & Galaxy 2.5-10
		2-1/2" ROLLED EDGE	26	26	10	29 3/8	29 3/8	27	27	8 1/4	5	13	5	3
		SURFACE MOUNTED	29 3/16		10 1/2	29 3/8	29 3/8	-	-	-		n Red		
		FLAT TRIM 3/8" •	16	40	9	19 3/8	43 3/8	17	41	8 7/8	4 1/4	4	4 1/4	DUAL EXTINGUISHER &
	8026	1-1/4" SQUARE EDGE	16	40	9	19 3/8	43 3/8	17	41	7 7/8	4 1/4	4	4 1/4	FD VALVE CABINET:
		2-1/2" ROLLED EDGE	16	40	9	19 3/8	43 3/8	17	41	7 1/4	4 1/4	4	4 1/4	Cosmic or Galaxy Extinguisher
	8023	SURFACE MOUNTED	19 3/16	43 3/16	9 1/2	19 3/8	43 3/8	-	-	-	Upo	n Red	luest	