

REGULAR
BC DRY CHEMICAL



WHEN
SECONDS
COUNT.



**Built Tough and
Ready to Serve**

- Modified universal valve body
- Accepts both pin or fork wall hooks
- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)

**STRIKE FIRST Regular
BC Fire Extinguishers are designed for:**



B FLAMMABLE
LIQUIDS
& GASES



C ELECTRICAL
EQUIPMENT



LISTED

MEETS OR EXCEEDS:
ANSI/UL 299 & 711



LISTED
HOMOLOGUÉ

MEETS OR EXCEEDS:
CAN/ULC-S504 & S508



Manufacturing
Fire Equipment
for over 35 Years



CAPACITY	2.75 lbs	5 lbs	10 lbs	20 lbs
Model No.	SF-SB275	SF-SB5	SF-SB10	SF-SB20
UL/ULC Rating	10-B : C	10-B : C	60-B : C	80-B : C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)
Discharge Time	9 sec	13 sec	15 sec	28 sec
PSI	150	195	235	235
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	21 1/4" (54 cm)	24" (61 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)
Weight	4 3/4 lb (2.2 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)
Chrome Option	YES	-	YES	-
Standard Bracket	Vehicle	Wall or Vehicle / Marine	Wall / VB	Wall / VB
Optional Brackets	Wall UP2 UP-DB	UB5 UB5-DB UP5-MD HDVB-1	UP-10MD HDVB-2	HDVB-3



STRIKE FIRST
FIRE EXTINGUISHERS