

FIRE EXTINGUISHERS - COSMIC MULTI PURPOSE DRY CHEMICAL - C - PORTABLE HANDHELD

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.



CLASS A FIRES

Common
Combustibles



CLASS B FIRES

Flammable
Liquids
and Gases



CLASS C FIRES

Energized
Electrical
Equipment

SPECIFICATIONS:

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

Temperature Range: -65° F (-53° C) to 120° F (49° C)

Construction: Heavy-duty steel cylinder with siphon tube, replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact-resistant powder coat finish.

Valve Material: Aluminum

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Description	Type	Valve	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol.	UL Rating 	Optional Mounting Bracket	USCG Approved
	FE02C	Cosmic 2-1/2E*	ABC Dry Chemical	Aluminum	2-½ lbs.	5-½ lbs.	3-¾"	15-½"	5-¾"	.2 cu.ft.	1A-10B:C	MB817C*	YES
	FE05C	Cosmic 5E			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¼"	.35 cu.ft.	3A-40B:C	MB818C	
	FE05BC	Cosmic 5B*			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¼"	.35 cu.ft.	3A-40B:C	MB818C*	
	FE10C	Cosmic 10E			10 lbs.	18-¼ lbs.	5-⅝"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C	
	FE20C	Cosmic 20E			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C	
	FE05CBV	Cosmic 5E		Brass	5 lbs.	10 lbs.	4-¼"	16-¾"	7-¼"	.35 cu.ft.	3A-40B:C	MB818C	
	FE10CBV	Cosmic 10E			10 lbs.	18-¼ lbs.	5-⅝"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C	
	FE20CBV	Cosmic 20E			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C	

*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.



JL INDUSTRIES

9702 Newton Ave S. Bloomington, MN 55431 | Many Locations Across North America

© 2026 Activar Construction Products Group, Inc.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.

6-10-2026

Distributor:	Project:
Contractor:	Approved By:
Date:	Architect:
Scale: N/A	Pages: 1 of 1
	Item #: